



EQUIPMENT REQUIRED

1. Dry dust mop
2. Auto-scrubber, low-speed rotary or cylindrical (max 350 RPM)
3. Buffing pads
4. Microfiber wet mop (do not use oil treated mops)

DAILY MAINTENANCE

Maintenance Type	Equipment Used	Cleaning Products	Cleaning Methods
Manual	<ul style="list-style-type: none">• Dry dust mop• Microfiber wet mop	StaticWorx ScrubWorx pH-neutral cleaner	<ol style="list-style-type: none">1. Sweep flooring surface2. Wash with mop using ScrubWorx cleaner3. Rinse floor with clean water

Maintenance Type	Equipment Used	Cleaning Products	Cleaning Methods
Auto-scrubber	<ul style="list-style-type: none"> Dry dust mop Auto-scrubber 3M 5000 green scrub pad 	StaticWorx ScrubWorx pH-neutral cleaner	<ol style="list-style-type: none"> Sweep flooring surface Scrub using ScrubWorx cleaner Vacuum up solution

BIMONTHLY-MONTHLY MAINTENANCE

Maintenance Type	Equipment Used	Cleaning Products	Cleaning Methods
Auto-scrubber	<ul style="list-style-type: none"> Dry dust mop Auto-scrubber 3M 5100 red scrub pad 	StaticWorx ScrubWorx pH-neutral cleaner	<ol style="list-style-type: none"> Sweep flooring surface Scrub using ScrubWorx cleaner Vacuum up solution Rinse floor with clean water

INITIAL CLEANING & DEEP CLEANING

Maintenance Type	Equipment Used	Cleaning Products	Cleaning Methods
Auto-scrubber	<ul style="list-style-type: none"> Dry dust mop Auto-scrubber 3M 5000 green scrub pad (initial cleaning) 3M 5100 red scrub pad (deep cleaning) 	StaticWorx ScrubWorx pH-neutral cleaner	<ol style="list-style-type: none"> Sweep flooring surface Scrub using ScrubWorx cleaner Allow solution to sit for 5-10 minutes Repeat step 2 Vacuum up solution Rinse floor with clean water

NOTES

- These instructions are to be used as a guide and should be adapted to the site conditions and traffic patterns observed in the different areas where GroundLock Extreme tile has been installed.
- In areas where disinfection is required, always rinse with clean water after the application of the disinfectant as per their manufacturer instructions.
- Never use floor cleaners with pH higher than 11.
- Walk-off mats are recommended at the entrance to every room. Clean as needed on a regular basis.
- Use floor mats to prevent scratching from table and chair casters.
- Rubber feet on tables and chairs will stain vinyl floorcoverings. Use non-rubber protectors to prevent stains.
- Never apply any commercial or ESD floor finishes to GroundLock Extreme tile.