

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Trade name : GroundWorx Ultra - Primer B
Product code : GroundWorx Ultra - Primer B

1.2. Recommended use and restrictions on use

No additional information available

1.3. Supplier

StaticWorx
P.O. Box 1556, Williston, VT 05495
- USA-Vermont T 617-923-2000 -
F 617-467-5871 staticworx.com

1.4. Emergency telephone number

Emergency number : Chemtrec: 800-427-9300 (Outside USA) 703-527-3887

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Acute toxicity (oral) Category 4	H302	Harmful if swallowed
Acute toxicity (dermal) Category 3	H311	Toxic in contact with skin
Acute toxicity (inhalation) Category 4	H332	Harmful if inhaled
Skin corrosion/irritation Category 1B	H314	Causes severe skin burns and eye damage
Serious eye damage/eye irritation Category 1	H318	Causes serious eye damage
Skin sensitization Category 1	H317	May cause an allergic skin reaction
Reproductive toxicity Category 1B	H360	May damage fertility or the unborn child
Specific target organ toxicity (single exposure) Category 3	H336	May cause drowsiness or dizziness
Hazardous to the aquatic environment - Acute Hazard Category 3	H402	Harmful to aquatic life
Hazardous to the aquatic environment - Chronic Hazard Category 3	H412	Harmful to aquatic life with long lasting effects

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H302+H332 - Harmful if swallowed or if inhaled
H311 - Toxic in contact with skin
H314 - Causes severe skin burns and eye damage
H317 - May cause an allergic skin reaction
H318 - Causes serious eye damage
H336 - May cause drowsiness or dizziness
H360 - May damage fertility or the unborn child

GroundWorx Ultra - Primer B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Precautionary statements (GHS-US)	: H402 - Harmful to aquatic life H412 - Harmful to aquatic life with long lasting effects P201 - Obtain special instructions before use P202 - Do not handle until all safety precautions have been read and understood P260 - Do not breathe vapors P261 - Avoid breathing vapors P264 - Wash hands, forearms and face thoroughly after handling P270 - Do not eat, drink or smoke when using this product P271 - Use only outdoors or in a well-ventilated area P272 - Contaminated work clothing must not be allowed out of the workplace P273 - Avoid release to the environment P280 - Wear protective clothing P301+P312 - If swallowed: Call a doctor if symptoms persist. if you feel unwell P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting P302+P352 - If on skin: Wash with plenty of soap P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing P308+P313 - If exposed or concerned: Get medical advice/attention P310 - Immediately call a doctor if symptoms persist. P312 - Call a doctor if symptoms persist. if you feel unwell P321 - Specific treatment (see a doctor if symptoms do not go away. on this label) P322 - Specific treatment (see a doctor if symptoms do not go away. on this label) P330 - Rinse mouth P333+P313 - If skin irritation or rash occurs: Get medical advice/attention P361+P364 - Take off immediately all contaminated clothing and wash it before reuse P363 - Wash contaminated clothing before reuse P403+P233 - Store in a well-ventilated place. Keep container tightly closed P405 - Store locked up P501 - Dispose of contents/container to in accordance with local regulations
-----------------------------------	---

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

GroundWorx Ultra - Primer B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	GHS-US classification
O,O'-Bis(2-aminopropyl)polypropyleneglycol	(CAS No) 9046-10-0	30 - 40	Skin Corr. 1C, H314 Eye Dam. 1, H318 Aquatic Acute 3, H402 Aquatic Chronic 3, H412
Phenol,4-nonyl-,branched	(CAS No) 84852-15-3	20 - 30	Acute Tox. 4 (Oral), H302 Skin Corr. 1B, H314 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
1-Piperazine ethanamine	(CAS No) 140-31-8	5 - 15	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Skin Corr. 1A, H314 Skin Sens. 1, H317 Aquatic Chronic 3, H412
4-tert-butylphenol	(CAS No) 98-54-4	10 - 15	Skin Irrit. 2, H315 Eye Dam. 1, H318
1,3-bis(aminomethyl)benzene	(CAS No) 1477-55-0	5 - 10	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Corr. 1A, H314
Benzenemethanol	(CAS No) 100-51-6	2 - 8	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H332 Eye Irrit. 2A, H319 Aquatic Acute 2, H401
2-methyl-1,5-pentanediamine	(CAS No) 15520-10-2	0 - 5	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Skin Corr. 1A, H314

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

- First-aid measures general : Call a physician immediately.
- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor/physician if you feel unwell.
- First-aid measures after skin contact : Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Call a physician immediately.
- First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
- First-aid measures after ingestion : Rinse mouth. Do not induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects (acute and delayed)

- Symptoms/injuries : May cause drowsiness or dizziness.
- Symptoms/injuries after skin contact : Burns. May cause an allergic skin reaction.
- Symptoms/injuries after eye contact : Serious damage to eyes.
- Symptoms/injuries after ingestion : Burns.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Specific hazards arising from the chemical

Reactivity : The product is non-reactive under normal conditions of use, storage and transport.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Only qualified personnel equipped with suitable protective equipment may intervene. Do not breathe vapors.

GroundWorx Ultra - Primer B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Use only outdoors or in a well-ventilated area. Do not get in eyes, on skin, or on clothing. Do not breathe vapors.
Hygiene measures : Separate working clothes from town clothes. Launder separately. Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Benzenemethanol (100-51-6)		
Not applicable		
1,3-bis(aminomethyl)benzene (1477-55-0)		
ACGIH	Local name	m-Xylene α,α' -diamine
ACGIH	ACGIH Ceiling (mg/m ³)	0.1 mg/m ³ (m-Xylene alfa,alfa'-diamine; USA; Momentary value; TLV - Adopted Value)
ACGIH	Remark (ACGIH)	Eye, skin, & GI irr
Phenol,4-nonyl-,branched (84852-15-3)		
Not applicable		
O,O'-Bis(2-aminopropyl)polypropyleneglycol (9046-10-0)		
Not applicable		
1-Piperazine ethanamine (140-31-8)		
Not applicable		
4-tert-butylphenol (98-54-4)		
Not applicable		
2-methyl-1,5-pentanediamine (15520-10-2)		
Not applicable		

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves

Eye protection:

Safety glasses

GroundWorx Ultra - Primer B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Wear respiratory protection

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: straw colored liquid
Odor	: Amine-like
Odor threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: > 400 °F
Flash point	: > 230 °F
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Solubility	: No data available
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Oral: Harmful if swallowed. Dermal: Toxic in contact with skin. Inhalation: Harmful if inhaled.

GroundWorx Ultra - Primer B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

GroundWorx Ultra - Primer B	
ATE US (oral)	500 mg/kg body weight
ATE US (dermal)	300 mg/kg body weight
ATE US (gases)	4500 ppmV/4h
ATE US (vapors)	11 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h
Benzenemethanol (100-51-6)	
LD50 oral rat	1620 mg/kg (Rat; Experimental value)
LD50 dermal rabbit	> 2000 mg/kg (Rabbit; Inconclusive, insufficient data)
ATE US (oral)	1620 mg/kg body weight
ATE US (gases)	4500 ppmV/4h
ATE US (vapors)	11 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h
1,3-bis(aminomethyl)benzene (1477-55-0)	
LD50 oral rat	930 mg/kg (Rat)
LD50 dermal rabbit	2000 mg/kg (Rabbit)
LC50 inhalation rat (mg/l)	2.4 mg/l/4h (Rat)
ATE US (oral)	930 mg/kg body weight
ATE US (dermal)	2000 mg/kg body weight
ATE US (vapors)	2.4 mg/l/4h
ATE US (dust, mist)	2.4 mg/l/4h
Phenol,4-nonyl-,branched (84852-15-3)	
LD50 oral rat	1882 mg/kg (Rat; Other; Experimental value; 1412 mg/kg bodyweight; Rat; Experimental value)
ATE US (oral)	1882 mg/kg body weight
ATE US (dermal)	2040 mg/kg body weight
1-Piperazine ethanamine (140-31-8)	
ATE US (oral)	1470 mg/kg body weight
ATE US (dermal)	880 mg/kg body weight
4-tert-butylphenol (98-54-4)	
LD50 oral rat	> 2000 mg/kg (Rat; OECD 401: Acute Oral Toxicity; Experimental value)
LC50 inhalation rat (mg/l)	> 5.6 mg/l/4h (Rat; Experimental value)
ATE US (oral)	3370 mg/kg body weight
ATE US (dermal)	2621 mg/kg body weight
2-methyl-1,5-pentanediamine (15520-10-2)	
LD50 oral rat	1690 mg/kg (Rat)
ATE US (oral)	1690 mg/kg body weight

Skin corrosion/irritation : Causes severe skin burns and eye damage.
Serious eye damage/irritation : Causes serious eye damage.
Respiratory or skin sensitization : May cause an allergic skin reaction.
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

Reproductive toxicity : May damage fertility or the unborn child.
Specific target organ toxicity – single exposure : May cause drowsiness or dizziness.

Specific target organ toxicity – repeated exposure : Not classified

Aspiration hazard : Not classified
Symptoms/injuries : May cause drowsiness or dizziness.

GroundWorx Ultra - Primer B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/injuries after skin contact	: Burns. May cause an allergic skin reaction.
Symptoms/injuries after eye contact	: Serious damage to eyes.
Symptoms/injuries after ingestion	: Burns.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Harmful to aquatic life with long lasting effects. Harmful to aquatic life.

Benzenemethanol (100-51-6)	
LC50 fish 1	460 mg/l (LC50; EPA OPP 72-1; 96 h; Pimephales promelas; Static system; Fresh water; Experimental value)
1,3-bis(aminomethyl)benzene (1477-55-0)	
EC50 Daphnia 1	16 mg/l (EC50; 48 h)
LC50 fish 2	> 100 mg/l (LC50; 96 h)
Threshold limit algae 1	12 mg/l (EC50; 72 h)
Phenol,4-nonyl-,branched (84852-15-3)	
EC50 Daphnia 2	0.085 mg/l (EC50; ASTM E729-88; 48 h; Daphnia magna; Semi-static system; Fresh water; Experimental value)
Threshold limit algae 2	0.027 mg/l (EC50; EPA OTS 797.1050; 96 h; Skeletonema costatum; Static system; Salt water; Experimental value)
1-Piperazine ethanamine (140-31-8)	
LC50 fish 1	> 100 mg/l (LC50; OECD 203: Fish, Acute Toxicity Test; 96 h; Oncorhynchus mykiss; Semi-static system; Fresh water; Experimental value)
EC50 Daphnia 1	58 mg/l (EC50; OECD 202: Daphnia sp. Acute Immobilisation Test; 48 h; Daphnia magna; Static system)
Threshold limit algae 2	> 1000 mg/l (EC50; OECD 201: Alga, Growth Inhibition Test; 72 h; Selenastrum capricornutum; Fresh water)
4-tert-butylphenol (98-54-4)	
EC50 Daphnia 1	3.9 mg/l (EC50; 48 h)
LC50 fish 2	5.14 mg/l (LC50; 96 h)
Threshold limit algae 2	11.2 mg/l (EC50; 72 h)
2-methyl-1,5-pentanediamine (15520-10-2)	
LC50 fish 1	130 mg/l (LC50; 48 h)

12.2. Persistence and degradability

Benzenemethanol (100-51-6)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. No (test)data on mobility of the substance available.
Biochemical oxygen demand (BOD)	1.6 g O ₂ /g substance
Chemical oxygen demand (COD)	2.4 g O ₂ /g substance
ThOD	2.5 g O ₂ /g substance
1,3-bis(aminomethyl)benzene (1477-55-0)	
Persistence and degradability	Not readily biodegradable in water.
Phenol,4-nonyl-,branched (84852-15-3)	
Persistence and degradability	Inherently biodegradable. Biodegradability in soil: no data available. Adsorbs into the soil. Photodegradation in the air.
1-Piperazine ethanamine (140-31-8)	
Persistence and degradability	Not readily biodegradable in water. Low potential for mobility in soil.
Chemical oxygen demand (COD)	0.56 g O ₂ /g substance
4-tert-butylphenol (98-54-4)	
Persistence and degradability	Readily biodegradable in water. Low potential for mobility in soil. Photolysis in the air.
ThOD	2.77 g O ₂ /g substance

GroundWorx Ultra - Primer B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2-methyl-1,5-pentanediamine (15520-10-2)	
Persistence and degradability	Biodegradability in water: no data available.

12.3. Bioaccumulative potential

Benzenemethanol (100-51-6)	
Log Pow	1-1.1, Experimental value; Other; 20 °C
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

1,3-bis(aminomethyl)benzene (1477-55-0)	
BCF fish 1	< 2.7 (BCF)
Log Pow	0.15
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

Phenol,4-nonyl-,branched (84852-15-3)	
BCF fish 1	271 (BCF; 480 h; Pimephales promelas)
BCF fish 2	1200/1300,BCF; OECD 305: Bioconcentration: Flow-Through Fish Test; 32 days; Gasterosteus aculeatus; Flow-through system; Salt water; Experimental value; Fresh weight
Log Pow	3.28 (OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method; 5.4; Experimental value; OECD 117: Partition Coefficient (n-octanol/water), HPLC method; 23 °C)
Bioaccumulative potential	Potential for bioaccumulation (500 ≤ BCF ≤ 5000).

1-Piperazine ethanamine (140-31-8)	
BCF fish 1	<= >0.3<=6.3,BCF; OECD 305: Bioconcentration: Flow-Through Fish Test; >4<=6 weeks; Cyprinus carpio; Flow-through system; Fresh water; Read-across
Log Pow	-1.48 (Experimental value; OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method; 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

4-tert-butylphenol (98-54-4)	
BCF fish 1	120 (BCF; 3 h)
BCF fish 2	20 - 88 (BCF)
BCF other aquatic organisms 1	34 (BCF; 24 h; Chlorella sp.)
BCF other aquatic organisms 2	240 (BCF; 5 h; Bacteria)
Log Pow	3 (Experimental value; OECD 117: Partition Coefficient (n-octanol/water), HPLC method; 23 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

2-methyl-1,5-pentanediamine (15520-10-2)	
Log Pow	0.27 (Estimated value)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

12.4. Mobility in soil

Benzenemethanol (100-51-6)	
Surface tension	0.04 N/m (20 °C)

Phenol,4-nonyl-,branched (84852-15-3)	
Log Koc	log Koc,Other; >= 4.35 - <= 5.69; Experimental value; GLP

1-Piperazine ethanamine (140-31-8)	
Log Koc	log Koc,4.57; Read-across; GLP

4-tert-butylphenol (98-54-4)	
Log Koc	log Koc,3.1; QSAR

12.5. Other adverse effects

Effect on the global warming : No known effects from this product.
GWPmix comment : No known effects from this product.

GroundWorx Ultra - Primer B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN2735 Amines, liquid, corrosive, n.o.s. (O,O'-Bis(2-aminopropyl)polypropyleneglycol,Phenol,4-nonyl-,branched), 8, III

UN-No.(DOT) : UN2735

Proper Shipping Name (DOT) : Amines, liquid, corrosive, n.o.s.
O,O'-Bis(2-aminopropyl)polypropyleneglycol,Phenol,4-nonyl-,branched

Class (DOT) : 8 - Class 8 - Corrosive material 49 CFR 173.136

Packing group (DOT) : III - Minor Danger

Hazard labels (DOT) : 8 - Corrosive



DOT Packaging Non Bulk (49 CFR 173.xxx) : 203

DOT Packaging Bulk (49 CFR 173.xxx) : 241

DOT Symbols : G - Identifies PSN requiring a technical name

DOT Special Provisions (49 CFR 172.102) : IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).
T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3)
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.
TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) : 154

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 5 L

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

DOT Vessel Stowage Other : 52 - Stow "separated from" acids

Emergency Response Guide (ERG) Number : 153

Other information : No supplementary information available.

TDG

Not applicable

Transport by sea

Not applicable

Air transport

Not applicable

GroundWorx Ultra - Primer B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 15: Regulatory information

15.1. US Federal regulations

GroundWorx Ultra - Primer B

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Benzenemethanol (100-51-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

1,3-bis(aminomethyl)benzene (1477-55-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Phenol,4-nonyl-,branched (84852-15-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

O,O'-Bis(2-aminopropyl)polypropyleneglycol (9046-10-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

1-Piperazine ethanamine (140-31-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

4-tert-butylphenol (98-54-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

2-methyl-1,5-pentanediamine (15520-10-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. US State regulations

1,3-bis(aminomethyl)benzene (1477-55-0)

U.S. - New Jersey - Right to Know Hazardous Substance List

1-Piperazine ethanamine (140-31-8)

U.S. - New Jersey - Right to Know Hazardous Substance List

SECTION 16: Other information

Other information

: Disclaimer: This SDS to the best of our knowledge conforms to the requirements of OSHA 20 CFR 1910.1200 and summarizes the health and safety hazard information and general guidance on how to safely handle the material at the date of issue. Each user must review the SDS in the context of how the product will be handled and used in the workplace.

GroundWorx Ultra - Primer B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases:

H227	Combustible liquid
H302	Harmful if swallowed
H311	Toxic in contact with skin
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H332	Harmful if inhaled
H336	May cause drowsiness or dizziness
H360	May damage fertility or the unborn child
H400	Very toxic to aquatic life
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

NFPA health hazard


: 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given.

NFPA fire hazard

: 1 - Must be preheated before ignition can occur.

NFPA reactivity

: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



HMIS III Rating

Health : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given

Flammability : 1 Slight Hazard - Materials that must be preheated before ignition will occur. Includes liquids, solids and semi solids having a flash point above 200 F. (Class IIIB)

Physical : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product